

AMENDMENTS TO THE SPECIFICATION

Please replace the following paragraphs of the specification. Applicant includes herewith an Attachment for Specification Amendments showing a marked up version of each replacement paragraph.

Please replace the paragraph beginning on page 8, line 17 with the following amended paragraph:

In order not to have to make use of the so-called Danish trolleys during transport of a stack of carriers, a certain part of a set of carriers can be provided with wheels ~~[[18]]~~ 28, as shown in FIG. 3. It is herein easy to travel with a stack of 5 to 6 of these carriers without further assist means.

Please replace the paragraph beginning on page 9, line 29 with the following amended paragraph:

FIG. 6 shows in more detail the construction of an L-shaped profile 19 and the supports 20 and 22 connected thereto. This shows that a recess is made in the L-shaped profile, in which a carrying bracket 24 is placed. This carrying bracket 24 is for instance bent out of round bar and fixed in L-shaped profile 19 by means of a welded connection. Carrying bracket 24 herein protrudes relative to L-shaped profile ~~[[10]]~~ 19 so as to rest on the bracket 20 of the other end of a corresponding carrier.

Please replace the paragraph beginning on page 10, line 18 with the following amended paragraph:

Welded onto the horizontal part of the Z-shaped profile are tubular brackets 33, which serve as supports. The brackets 33 are provided on their upper side with holes 34 for receiving pins ~~[[35]]~~ (not shown) of the carrier stacked onto the brackets. ~~[[Pins 35 are]]~~ The pins may be welded onto the underside of the horizontal part of the Z-shaped profile.